



PRODUCT BULLETIN

AROPLAZ® 6129-Z-65

Polyester

DESCRIPTION

AROPLAZ® 6129-Z-65 is a linear saturated polyester for flexible melamine crosslinked baking enamels.

FEATURES & BENEFITS

- High flexibility

PROPERTIES - LIQUID

Percent Solids, Weight	65
Percent Solids, Volume	57.2 approx.
Viscosity at 25°C	
Stokes	22.7 - 36.2
Gardner-Holdt	Z – Z ₂
Color, Gardner	3 max.
Hydroxyl Value, Solids	25 – 40
Acid Value, Solids	10 max.
Pounds per Gallon, Solution	9.10
Specific Gravity, 25/25°C	1.095 approx.
Flash Point (SFCC), Typical	138°F
Solvent	Aromatic 150 / Butyl Cellosolve (75 / 25%)

APPLICATIONS

- Coil coating applications requiring high flexibility

SHELF LIFE & STORAGE

Store in a cool, dry place, preferably under 80°F to ensure a useful shelf life of at least two years.

SAFETY & WARRANTY

To receive a copy of our safety and warranty information, please email safetyandwarranty@polynt.com.

AROPLAZ® 6129-Z-65

Polynt Composites USA Inc. | +1 800 322 8103 | 99 East Cottage Avenue, Carpentersville, IL 60110 USA

www.polynt.com

Page 1 of 1 (March 2021)